

**Product Description**

EZ PLUG is a ready to use, quick setting cement designed for stopping water leakage instantly. It is suitable to use in both dry and water seepage conditions.

**Uses & Applications**

Use to stop pressure leaks and seepage through rock and concrete in water tank, pools, tunnels, basements, subways, culverts, dams, etc.

**Key Benefits**

- Rapid set, stop water instantly and permanently.
- Easy to use, just add water.
- Chloride free.
- Non cracking when set.
- Good adhesion to concrete substrate.



**Technical Data**

CHARACTERISTICS	RESULTS	TEST METHOD
Appearance	Grey powder	-
Mixed Density	1.9 ± 0.1	ASTM D1475
pH	11	-
Hardening Time	45 – 60 seconds	-

**Application Instructions**

*Substrate Preparation*

- Cut or chip concrete in “V” shape around the leaking area. Remove all loose particles, and clean the surface thoroughly with water.

*Application*

- Mix CLEVCON EZ PLUG with water. It is recommended to mix in small quantities at a time.

Mixing Ratio	By weight
EZ PLUG	1 kg
Water	Approx. 0.2 – 0.3 kg

WATERPROOFING SYSTEM

- Work from outside toward the center of the leak. Plug mixed cement and hold it for about 1 minute.
- The excess material can level off with steel trowel.

#### Safety Instructions

Wear appropriate protective equipment such as gloves, safety glasses or goggles, protective clothing during use. In case of eye contact: promptly wash eyes with plenty of water. Continue to rinse for at least 15 minutes and consult physician immediately.

#### Packing

5 kg. per pail.  
20 kg. per pail.

#### Storage & Shelf Life

Material must be kept in-door at room temperature, avoid expose of direct sunlight. Product Shelf life is 6 months in unopened package and under suitable storage condition.

Disclaimer: The information provided in this document is based on our knowledge and experience of the product. In actual application results may vary because of site conditions, application methods and other factors that beyond our control. Users are recommended to test out product performance before actual use. Any data contained in this document, including our sale person or staff consultation is in no way constitutes a warranty relative to the use of our products. Our general terms and conditions of sales shall prevail. The superseded version of this datasheet may be issued without prior notice. Customers and users are encouraged to check with our staffs for the latest version of this document.

CLEVCON (THAILAND) CO., LTD.  
14/12 Moo 5, Bung Kham Proi., Lam Luk Ka, Pathum Thani, Thailand 12150  
Tel: +66-2-569-1540 • Fax: +66-2-569-1541  
Email: [clevconthailand@gmail.com](mailto:clevconthailand@gmail.com) • Website: [www.clevconthai.com](http://www.clevconthai.com)



ISO 9001:2015 Certified