

Product Description

EZ RELEASE-ECO is economical grade oil-based form release agent used to prevent adhesion between concrete and forming surfaces. EZ Release-ECO can be used with all types of concrete forms. It keeps concrete stain-free and residue-free, ready to receive paints, mortar, plaster or other topping.

Uses & Applications

Can be used for casting of typical structure such as column, beam, slab, wall, concrete pipe, pile, and for architectural concrete such as precast panel, flat ceiling slab or post-tension slab.

Key Benefits

- Good weather resistance.
- Effective on all types of forms: wooden, steel, and plastic.
- Easy to release and to clean.
- Increase the life of form.
- Prevent metal form from rust.
- Clean concrete surface.

Technical Data

PROPERTIES	VALUE
Appearance	Dark Brown liquid
Specific Gravity	0.90 ± 0.05
Viscosity	300 – 400 mm ² /S
Flash point	More than 100 °C

Application Instructions

- EZ RELEASE-ECO can be applied by brush, sprayer or other convenient methods.

Approximate Coverage:

- 35-50 m² / liter with brush on metal or plastic forms.
- 20-35 m² / liter with brush on wooden form.

Safety Instructions

- Wear gloves, goggles, and necessary protective equipment during use.
- Avoid directly inhaling of chemical.
- Do not use around flammable area.
- If eye contact, rinse with water and consult physician immediately.

Packing

200 Liter per drum.
25 Liter per can.

Storage & Shelf Life

Material must be kept in-door, avoid of direct sunlight and humidity. It should be stored at room temperature. In proper storage condition and unopened package, shelf life is 12 months.

FORMWORK AID AGENT

Disclaimer: The information provided in this document is based on our knowledge and experience of the product. In actual application results may vary because of site conditions, application methods and other factors that beyond our control. Users are recommended to test out product performance before actual use. Any data contained in this document, including our sale person or staff consultation is in no way constitutes a warranty relative to the use of our products. Our general terms and conditions of sales shall prevail. The superseded version of this datasheet may be issued without prior notice. Customers and users are encouraged to check with our staffs for the latest version of this document.

CLEVCON (THAILAND) CO., LTD.
14/12 Moo 5, Bung Kham Proi., Lam Luk Ka, Pathum Thani, Thailand 12150
Tel: +66-2-569-1540 • Fax: +66-2-569-1541
Email: clevconthailand@gmail.com • Website: www.clevconthai.com



ISO 9001:2015 Certified