

Product Description

RELEASE-R is ready-to-use water-based concrete form release agent. When applied it forms the water resistance chemical barrier to prevent concrete sticking. It provides ease release of formworks, eliminating concrete repairs, while keeping concrete stain-free and residue-free, ready to receive paints, mortar, plaster or other topping.

Uses & Applications

EZ RELEASE-R can be used for casting of all types of concrete works such as column, beam, slab, wall, concrete pipe, pile, etc.

Key Benefits

- Economical
- Ready to use, no mixing required.
- Effective on all types of forms: wooden, steel, and plastic.
- Easy to release and to clean.
- Increase the life of form.
- Non-staining.
- Low odor compared to oil-based.
- Safe for user.

Technical Data

PROPERTIES	VALUE
Appearance	Milky White liquid
Specific Gravity	0.98 ± 0.02

Application Instructions

- Use brush or sprayer to apply the release agent for 1-2 times depending on porosity of the form surface.

Approximate Coverage:

- 35-50 m² / litre with brush on metal or plastic forms.
- 20-35 m² / litre with brush on wooden form.

Safety Instructions

Wear gloves, goggles, and necessary protective equipment during use. If eye contact, rinse with water and consult physician immediately.

Packing

200 Liter per drum.
25 Liter per can.

Storage & Shelf Life

Material must be kept in-door, avoid of direct sunlight and humidity. It should be stored at room temperature. In proper storage condition and unopened package, shelf life is 12 months.

FORMWORK AID AGENT

Disclaimer: The information provided in this document is based on our knowledge and experience of the product. In actual application results may vary because of site conditions, application methods and other factors that beyond our control. Users are recommended to test out product performance before actual use. Any data contained in this document, including our sale person or staff consultation is in no way constitutes a warranty relative to the use of our products. Our general terms and conditions of sales shall prevail. The superseded version of this datasheet may be issued without prior notice. Customers and users are encouraged to check with our staffs for the latest version of this document.

CLEVCON (THAILAND) CO., LTD.
14/12 Moo 5, Bung Kham Proi., Lam Luk Ka, Pathum Thani, Thailand 12150
Tel: +66-2-569-1540 • Fax: +66-2-569-1541
Email: clevconthailand@gmail.com • Website: www.clevconthai.com



ISO 9001:2015 Certified