

Product Description

PRIMER-S is solvent based acrylic primer with high penetration and bonding properties. It improves bonding between substrate and the coatings, reduces peel-off, protects surface against moisture and chloride, extends the service life of waterproofing system.

Uses & Applications

Use as primer for roof waterproofing system on new and old concrete.

Key Benefits

- High bonding strength.
- Fast dry, easy application.

Technical Data

CHARACTERISTICS	RESULTS
Appearance	Clear liquid
Specific Gravity	0.91 ± 0.02
Solid Content	35 ± 2%
Touch Dry	15 minutes
Drying Time	30 - 60 minutes

Application Instructions

- The substrate should be clean and sound, free of dust loose particles, grease, oil, primers from previous membrane systems or bitumen.
- Apply by brush or roller. Let dry for 60 minutes.

Consumption Rate	Coverage per pail
0.15-0.2 liter/sq.m.	90 - 120 sq.m.

* Coverage rate may vary due to porosity of surface including application method. Field trials are recommended.

Safety Instructions

Wear appropriate protective equipment such as gloves, safety glasses or goggles, protective clothing during use. In case of eye contact: promptly wash eyes with plenty of water. Continue to rinse for at least 15 minutes and consult physician immediately.

Packing

18 Liter per pail

Storage & Shelf Life

Material must be kept in-door at room temperature, avoid expose of direct sunlight. Product Shelf life is 12 months in unopened package and under suitable storage condition.

Disclaimer: The information provided in this document is based on our knowledge and experience of the product. In actual application results may vary because of site conditions, application methods and other factors that beyond our control. Users are recommended to test out product performance before actual use. Any data contained in this document, including our sale person or staff consultation is in no way constitutes a warranty relative to the use of our products. Our general terms and conditions of sales shall prevail. The superseded version of this datasheet may be issued without prior notice. Customers and users are encouraged to check with our staffs for the latest version of this document.

CLEVCON (THAILAND) CO., LTD.
14/12 Moo 5, Bung Kham Proi., Lam Luk Ka, Pathum Thani, Thailand 12150
Tel: +66-2-569-1540 • Fax: +66-2-569-1541
Email: clevconthailand@gmail.com • Website: www.clevconthai.com



ISO 9001:2015 Certified