

**Product Description**

SWELL ADHESIVE is a water-based bonding agent used for installation of Clevcon Hyperswell waterstop. Waterstop Adhesive is easy to apply and has excellent bonding property on most types of substrate. It is used to secure waterstop in the desired position prior to pouring of concrete.

**Technical Data**

CHARACTERISTICS	RESULTS	TEST METHOD
Appearance	Milky white liquid	-
Specific Gravity	1.01 – 1.02	ASTM D1475
pH	7 - 8	-

**Application Instructions**

- Ensure dried and cleaned substrate prior to application of Swell Adhesive.
- Use brush or roller to apply the adhesive on substrate for the width at least equal to the profile of chosen waterstop.
- Allow adhesive to dry and become tacky for a few minutes, press waterstop firmly on the adhesive along the joints.

Coverage rate: 30-40 meters per liter.

**Safety Instructions**

Wear protective equipment such as gloves, safety glasses or goggles, protective clothing during use. In case of eye contact: promptly wash eyes with plenty of water and consult physician immediately.

**Sizes & Packing**

5 liters plastic can.

**Storage & Shelf Life**

Product must be stored at room temperature. Keep out of direct sunlight.

Shelf life is 12 months in unopened package.

Disclaimer: The information provided in this document is based on our knowledge and experience of the product. In actual application results may vary because of site conditions, application methods and other factors that beyond our control. Users are recommended to test out product performance before actual use. Any data contained in this document, including our sale person or staff consultation is in no way constitutes a warranty relative to the use of our products. Our general terms and conditions of sales shall prevail. The superseded version of this datasheet may be issued without prior notice. Customers and users are encouraged to check with our staffs for the latest version of this document.

CLEVCON (THAILAND) CO., LTD.  
14/12 Moo 5, Bung Kham Proi., Lam Luk Ka, Pathum Thani, Thailand 12150  
Tel: +66-2-569-1540 • Fax: +66-2-569-1541  
Email: [clevconthailand@gmail.com](mailto:clevconthailand@gmail.com) • Website: [www.clevconthai.com](http://www.clevconthai.com)



ISO 9001:2015 Certified